

# Hi-VNI® Technology on the GO

**Ambulate** and **Transfer** patients without compromising respiratory support.

- Maintain L/min rate, FiO<sub>2</sub>, temperature, and humidification levels
- Seamless transition from cylinders to wall gas
- Easy hot swap of patient circuit onto a stationary unit



**Enhanced with new light, fast charging Lithium-ion battery**

## Technical Specifications

The Vapotherm Transfer Unit includes the Precision Flow® roll stand, medical grade mobile power system, Gas Manifold, and E cylinder holder

## Performance

Allows the mobile delivery of Hi-VNI Technology within a hospital environment.

# Hi-VNI® Technology on the GO

**Tank gas supply:** Mobile run time will vary depending on the O<sub>2</sub>/air blend and L/min rate settings on the Precision Flow.

Sample Estimates		
L/min Rate	FiO <sub>2</sub>	Approximate Time in Minutes
4	50%	170
4	100%	140
25	50%	27
25	21% or 100%	22
40	50%	17
40	21% or 100%	14

**Battery life:** Up to 1 hour.

**Recharging time:** Less than 3 hours, as displayed on the remote user interface.

## System Requirements

- 100 to 240 VAC Universal Input (to charge battery)
- Oxygen E-Cylinder regulated to 60 psi
- Oxygen E-Cylinder regulator (not included)
- Air E-Cylinder regulated to 60 psi
- Air E-Cylinder regulator (US Only)
- Vapotherm Precision Flow or Precision Flow Plus

