

Hi-VNI® Technology on the GO

Ambulate and **Transfer** patients without compromising respiratory support.

- Maintain L/min rate, FiO₂, temperature, and humidification levels
- Seamless transition from cylinders to wall gas
- Easy hot swap of patient circuit onto a stationary unit



Enhanced with new light, fast charging Lithium-ion battery

Technical Specifications

The Vapotherm Transfer Unit includes the Precision Flow® roll stand, medical grade mobile power system, Gas Manifold, and E cylinder holder

Performance

Allows the mobile delivery of Hi-VNI Technology within a hospital environment.

Hi-VNI® Technology on the GO

Tank gas supply: Mobile run time will vary depending on the O₂/air blend and L/min rate settings on the Precision Flow.

Sample Estimates		
L/min Rate	FiO ₂	Approximate Time in Minutes
4	50%	170
4	100%	140
25	50%	27
25	21% or 100%	22
40	50%	17
40	21% or 100%	14

Battery life: Up to 1 hour.

Recharging time: Less than 3 hours, as displayed on the remote user interface.

System Requirements

- 100 to 240 VAC Universal Input (to charge battery)
- Oxygen E-Cylinder regulated to 60 psi
- Oxygen E-Cylinder regulator (not included)
- Air E-Cylinder regulated to 60 psi
- Air E-Cylinder regulator (US Only)
- Vapotherm Precision Flow or Precision Flow Plus

